



To us it's more than just water...

# 1665-2750 Calcite Filter

Commercial Automatic



## WATERWAYS

Quality ways with water

Est. 1987

**Product Description:** Calcite is a food grade safe to drink pH adjustment mineral readily absorbed via flow of water through the material. Calcite filters are used to raise pH in acidic waters to a neutral level, typically pH 7.0 is optimum. Low pH waters are very corrosive and outside of safe water guidelines.

### Specifications

Type	Automatic Calcite pH Correction Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	16" (41cm) x 65" (165cm) wound fibreglass pressure vessel	
Media	125kg of calcite	
Control Valve	Fleck 2750 automatic control valve Microprocessor time or volume activated backwash options	
Flow Rate	Continuous	70 litres per minute
	Peak	90 litres per minute
Pressure	Maximum	600 kpa (85 psi)
	Minimum	175 kpa (25 psi)
Pipe Sizes	Inlet/outlet	1" (25mm)
	Drain	3/4" (20mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Est. 1987 Australian Owned & Operated

**Waterways Products (Aust) Pty Ltd**  
23 Aldershot Road, Lonsdale SA 5160  
PO Box 443 Lonsdale DC SA 5160  
Telephone 08 8186 0189 Facsimile 08 8382 7488  
Email: [enquiries@waterwaysproducts.com](mailto:enquiries@waterwaysproducts.com)  
[www.waterwaysproducts.com](http://www.waterwaysproducts.com)