



To us it's more than just water...



2162-2850 Carbon Filter Commercial Automatic



Est-1987

WATERWAYS

Quality ways with water

Product Description: Carbon filters are used for water clarification (colour removal), bacterial capture/retention, chlorine removal and odour/taste removal. Carbon must be backwashed regularly to reduce the risk of bio-fouling occurring. Carbon filters don't cope well with sediment loads, it's therefore common to have a mixed bed filter installed prior to handle this.

Specifications

Type	Automatic Carbon Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	21" (53cm) x 62" (157cm) wound fibreglass pressure vessel	
Media	125kg of carbon	
Control Valve	Fleck 2850 3 stage regeneration Industrial valve Microprocessor backwash control	
Flow Rate	Continuous	110 litres per minute
	Peak	120 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	1 1/2" (40mm)
	Drain	1" (25mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Est-1987 Australian Owned & Operated

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160
PO Box 443 Lonsdale DC SA 5160
Telephone 08 8186 0189 Facsimile 08 8382 7488
Email: enquiries@waterwaysproducts.com
www.waterwaysproducts.com