

WATERWAYS

Quality ways with water

**Product Description:** Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

## **Specifications**

hore H

Туре	Automatic Mixed Bed Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	9" (23cm) x 48" (102cm) wound fibreglass pressure vessel	
Media	30kg of mixed media Sand, anthracite and gravels	
Control Valve	Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash	
Flow Rate	Continuous Peak	25 litres per minute 30 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	3/4" (20mm) 1/2" (12mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd 23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160

www.waterwaysproducts.com

Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com

WATERWAYS