



To us it's more than just water...



SA2 Mixed Bed Filter

Light Commercial Automatic



Est-1987

WATERWAYS

Quality ways with water

Product Description: Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

Specifications

Type	Automatic Mixed Bed Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Media	53kg of mixed media Sand, anthracite and gravels	
Control Valve	Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash	
Flow Rate	Continuous	35 litres per minute
	Peak	40 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	3/4" (20mm)
	Drain	1/2" (12mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Est-1987 Australian Owned & Operated

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160

PO Box 443 Lonsdale DC SA 5160

Telephone 08 8186 0189 Facsimile 08 8382 7488

Email: enquiries@waterwaysproducts.com

www.waterwaysproducts.com