

SM1
Mixed Bed Filter WARRANT

## **WATERWAYS**

Quality ways with water



**Product Description:** Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

## **Specifications**

Туре	Manual Mixed Bed Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	9" (23cm) x 48" (102cm) wound fibreglass pressure vessel	
Media	30kg of mixed media Sand, anthracite and gravels	
Control Valve	Fleck 2510 manual valve Fast backwash and rapid rinse Lever operation	
Flow Rate	Continuous Peak	25 litres per minute 30 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	3/4" (20mm) 1/2" (12mm)
Drain Contoller	Flow control size	Fleck # 700

Note: Product specifications are a guide only and can change without notice.

## Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com