



To us it's more than just water...



2162-2850 Water Softener

Commercial Automatic



Est-1987

WATERWAYS

Quality ways with water

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

Type	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	102,000 litres at 100 mg/l hardness	
Media Tank	21" (53cm) x 62" (157cm) wound fibreglass pressure vessel	
Resin Capacity	175 litres of fine mesh cation resin	
Control Valve	Fleck 2850 3 stage regeneration Industrial Valve Volume (on demand) regeneration	
Brine Tank	24" (61cm) x 50" (132cm) with lid	
Flow Rate	Continuous	115 litres per minute
	Peak	130 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	1 1/2" (40mm)
	Drain	1" (25mm)
Salt Usage	20kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Est-1987 Australian Owned & Operated

Waterways Products (Aust) Pty Ltd
23 Aldershot Road, Lonsdale SA 5160
PO Box 443 Lonsdale DC SA 5160
Telephone 08 8186 0189 Facsimile 08 8382 7488
Email: enquiries@waterwaysproducts.com
www.waterwaysproducts.com