

2472·2850Calcite Filter





WATERWAYS

Quality ways with water

Product Description: Calcite is a food grade safe to drink pH adjustment mineral readily absorbed via flow of water through the material. Calcite filters are used to raise pH in acidic waters to a neutral level, typically pH 7.0 is optimum. Low pH waters are very corrosive and outside of safe water guidelines.

Specifications

Туре	Automatic Calcite pH Correction Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	24" (61cm) x 72" (183cm) wound fibreglass pressure vessel	
Media	225kg of calcite	
Control Valve	Fleck 2850 3 stage regeneration Industrial valve Microprocessor backwash control	
Flow Rate	Continuous Peak	130 litres per minute 150 litres per minute
Pressure	Maximum Minimum	600 kpa (85 psi) 175 kpa (25 psi)
Pipe Sizes	Inlet/outlet Drain	1 1/2" (40mm) 1" (25mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com